




Contact Information

Please contact Ken Pomerantz in the Infrastructure Division for more information:

Ken Pomerantz
Planning & Development Department
Infrastructure Division
155 Johnston St.
P.O. Box 11706
Rock Hill, SC 29731
Ph.: 803-329-5558
Fax: 803-329-7228
Email: kpomerantz@cityofrockhill.com



Planning & Development Dept.
155 Johnston St.
P.O. Box 11706
Rock Hill, SC 29731
803-329-5590



Sidewalks and Curb and Gutter

What is acceptable?

What is unacceptable?



www.cityofrockhill.com

Sidewalks and Curb and Gutter

Unacceptable Curb & Gutter

Each crack in the curb and gutter needs to be saw cut and epoxied.

However, if there are more than two cracks in a section of curb and gutter, then the section needs to be removed and replaced.



Acceptable Curb & Gutter

This is considered as “top notch” curb and gutter.



Marking Curb & Gutter



For cracks that need to be epoxied, mark the crack with paint.

For partial sections to be replaced, mark with one arrow in the direction of the expansion joint .



For a complete section of curb and gutter to be replaced, place two arrows at each expansion joint to show limits.

Unacceptable Sidewalks

If the sidewalk is damaged, then the entire section (from expansion joint to expansion joint) must be removed and replaced.



Marking Sidewalk

Place an “X” on the sections of sidewalk that needs to be removed.



Acceptable Sidewalk



Additional Sidewalk Information

When forming and pouring sidewalk in a subdivision that is being built, there are two options:

- ❖ If the sidewalk will be poured prior to the house being built, then the sidewalk must be at least 6” thick.
- ❖ If the sidewalk will be poured after the house is built, then the sidewalk only has to be 4” thick.

